



DEAERATION FILTER MDH 250




Designed for tanks in mobile and industrial machines

PASSION TO PERFORM

DEAERATION FILTER

The MDH 250 “bubble-free” deaeration filter allows the reduction of air inflow into the tank through the filter. Thanks to its multiple connections and its differential indicator, it is adaptable to all systems.



APPLICATIONS

MOBILE EQUIPMENT

Agriculture & Forestry

Construction

Materials handling

Mining



INDUSTRIAL

Marine
& Offshore

Steel plant
& Metal Processing

Power Generation
(including renewable)

Forming
machines



FEATURES & BENEFITS

- Max working pressure 1 MPa (10 bar) - flow rate up to 500 l/min
- MDH 250 length 2 and 4
- Reduction of air inflow into the tank through the filter
- Improved deaeration performance of the filter in the tank
- Lower pressure loss and higher working pressure than standard tank top return filters
- Bypass valve on the top with bayonet mount
- Stronger bypass system reducing vibrations
- Diffuser, integrated in the filter
- Easier filter element replacement
- Internal external filtration; it is possible to remove the filter element along with all contaminant
- Flanged connections 1 1/4" and 1 1/2" SAE 3000
- Threaded connections 1", 1 1/4" and 1 1/2" GAS/NPT/SAE
- Differential indicators (DES and DVS) available as accessories

MDH Series >> **VS** >> STANDARD FILTERS


MDH 250



DEAERATION RETURN FILTER WITH HIGH FLOW RATE FLUID FLOW IN/OUT

- Multiple connections (multiport)
- Differential indicator
- Flanged connection
- Threaded connection

MDH filter with reduced air bubbles in the tank



MPH 250



STANDARD RETURN FILTER WITH HIGH FLOW RATE FLUID FLOW IN/OUT

- Up to 2 Flanged connections
- No differential indicator

MPFX 181



STANDARD TANK TOP RETURN FILTER FLUID FLOW OUT/IN

- 1 Threaded connection
- No differential indicator

WORLDWIDE NETWORK



CANADA • CHINA • FRANCE • GERMANY • INDIA • RUSSIAN FEDERATION

USA • UNITED KINGDOM • UNITED ARAB EMIRATES • SINGAPORE



PASSION TO PERFORM



mpfiltri.com